

INFORMATION FOR USERS

! Attention

1. Before hanging wallpapers place the pieces of wallpaper on a surface and make sure that both pieces and seams match.
2. Prime the wall.
3. Use the glue for heavy vinyl wallpaper with non-woven backing.
4. The glue is applied to the wall, according to the width of the each piece with extra 20 cm
5. Use only a rubber roller.
6. Keep wallpaper surface clean of glue.

VIDEO GUIDE



VIDEO GUIDE: <https://ffactura.ru/blog/wallpapering-instruction-by-factura>

1. STORAGE OF FACTURA WALLPAPER

1.1 Before hanging the wallpaper should be stored horizontally.

Release the wallpaper from the stretch wrap (If stored for more than one month).

2. FACTURA WALLPAPER CHECK


2.1. It is preferred to check the «FACTURA» wallpaper right after receiving, but always before you are going to hang it. Place the FACTURA wallpaper on a clean surface, identify the sequence of the pieces to hang, check how pieces of the image match together.

2.2. Manufacturing defects are print defects, pattern mismatch on pieces of more than 3 mm, separate pieces color difference, color difference between FACTURA wallpaper and color proof. A defect is not a color difference between the FACTURA wallpaper color and the color on a computer monitor.

3. FACTURA WALLPAPER PREPARATION

3.1 Place the wallpaper on a clean surface according to the pattern on them. If the wallpaper consist of several pieces, match them and make sure that the pattern is completely matched. Using a tape measure carefully check the size of the wallpaper and the surface to cover.

3.2 FACTURA wallpaper marking



1 - Bottom of the wall

2 - Piece number and total number of pieces

3 - Order number

4 - Manufacture date

4. PREPARING THE WALLS

4.1. Prepare the walls before wallpapering. Remove old wallpaper, dirt and stains. If the walls are painted, all paint must be removed.

4.2. If there are cracks and irregularities on the walls, they must be fixed.

4.3. The surface (including drywall sheets) must be flattened, plastered and coated with acrylic deep penetration primer. If there is no antiseptic in the primer, cover the surface additionally with an antiseptic

4.5. Various wall defects that were not removed while preparation can be visible after the wallpaper is hung and may affect the quality of wallpaper (so-called «bubbles» may appear on the wallpaper, as well as wallpaper seams mismatch, wallpaper peeling off, etc.)

4.6. The surface must be dry, flat, hard, slightly rough, firm, slightly absorbent, neutral (with no alkalines), with no dust, grease, cracks, irregularities, dirt, stains, paint traces.

4.7. Do not hang wallpaper on non completely dry walls. Otherwise unwanted color changes and wallpaper flaking may occur.

4.8. The humidity of the room where hanging wallpaper should be about 40%. Hang wallpaper at a room temperature 18-25 ° C.

4.9. The surface of the walls should be equally light.

5. HANGING WALLPAPER / GLUE

5.1. Use glue that is suitable for wallpaper type - **SEMIN or Quelyd SPETS-FLIZELIN**

5.2 Prepare and apply glue according to the manufacturer instructions.

5.3 Select the piece of wallpaper to hang first. Apply the glue evenly to the wall with a roller and brush. Apply the glue on the wall respectively to a wallpaper piece with extra 150mm to the right. Start hanging. If necessary, apply glue to the edges of the wallpaper with a brush and roll the seam with a special roller or wallpaper spatula. Wallpaper is hanging with no gaps between seams.

6. RECOMMENDATIONS

6.1. While hanging keep the wallpaper clean of glue as it leaves stains, and their complete removal is not guaranteed.

6.2. Glue stains can be removed with a wet cloth. Do not rub the glue over the wallpaper, it must be literally «rinsed off» and not rubbed off the surface.

6.3. Any glue excesses must be removed immediately before it dry, otherwise the glue may react with the ink layer and cause negative consequences.

6.4. Avoid drafts and temperature fluctuations during the wallpapering and drying process.

6.5. Do not ventilate or heat the wallpapered room, do not make other repairs until the wallpaper is dry

(at least 24 hours, preferably 48 hours).

6.6. Never use copying pencil, marker pens or ballpoint pens to mark surfaces.

6.7. When wallpapering do not rub the surface of the wallpaper for too long, do not scratch the wallpaper.

6.8 Wallpaper drying time 1-3 days. When drying do not open windows in the room where wallpaper was hung to avoid drafts. If air bubbles appeared on the wallpaper, they can be removed by using a wallpaper glue and a medical syringe with a thick needle. Fill the syringe with wallpaper glue, put on a needle, carefully pierce the bubble and squeeze a small amount of glue into the bubble. Smooth the bubble with a wallpaper spatula, squeezing the excess glue through the hole.

7. LIMITATION OF LIABILITY


7.1. The manufacturer is not responsible for damage to the FACTURA wallpaper due to improper storage, improper installation (hanging) and fixing of the FACTURA wallpaper, improper use, as well as due to intentional or careless damage to the wallpaper by third parties.

7.2 The manufacturer is not responsible for a possible discrepancy between the dimensions specified by the Customer and the actual dimensions of the surfaces on which the photo wallpaper to be installed and related image mismatch.

7.3 The manufacturer of the FACTURA wallpaper is not responsible for the complete or partial FACTURA wallpaper peeling off due to inappropriate surface preparation.

7.4 Claims of color mismatch, color defects, size discrepancy or poor-quality image after applying glue to at least one part of FACTURA wallpaper or after complete or partial hanging of FACTURA wallpaper are not accepted.



 8 (812) 900-87-96

 shop@ffactura.ru

 WWW.FFACTURA.RU

 vk.com/ffactura

 instagram.com/factura_wallpaper

 facebook.com/ffactura